


# Lipped Spigot

- A selection of BFM® T304L spigots are available with a 6mm deep 'lip' on the end of the tail
- This lip enables the spigot to be attached to compatible quick connect modular tubing/piping systems.
- The spigot lip clamps in place with corresponding modular lip using quick-release clamp systems.
- Eliminates the need for welding to attach the spigot to pipework.
- A BFM® Lipped Spigot has a 6mm shorter tail than the standard BFM® spigot ie. total spigot height is 83mm.
- To enable the installation of a TR (Tool Release) connector, a 6mm / 15/64" hole can be drilled in the top seat of the spigot head.



## PHYSICAL PROPERTIES:

Material	Stainless Steel T304L
Interior Finish	≤ 0.8Ra micro-metres (32Ra micro-inches)
Wall Thickness	2.0mm / 5/64"
Length/height (± 2mm) (for all diameters)	83mm / 3 1/4" (Head: 37mm / 1 1/2") (Tail: 46mm / 1 3/8")
Depth of Lip (± 1mm)	6mm / 15/64"

## AVAILABLE SIZES: (In 50mm (2") increments)

Diameters	Ø100mm* - 400mm (Ø4" - 16")
-----------	--------------------------------

(\* Ø100mm measured externally (OD) - all other diameters measured internally (ID). Note that there is a -1 / + 3mm tolerance on the tail diameter of all spigot sizes.)

*Note: For applications where there is a possibility for static build up, e.g. wood dust, flour, milk powder etc., we recommend using a static dissipative wire (strip), connecting the two BFM® spigots together.*